



Key to Symbols

-  Double Insulation / Full Insulation
-  SDS max
-  SDS-Max Quick Exchange System
-  Electronic Control
-  Bosch SDS
-  SDS-Click Quick Clamping System
-  Rotation Stop
-  Velcro Fastening
-  Constant Electronic
-  Turbo Blower
-  Forward / Reverse Rotation
-  Removable Cable
-  Overload Clutch
-  Torque Control
-  Spindle Lock
-  Restart Protection
-  Saw Blade Pendulum Action
-  Direct Cooling and Additional air Inlets
-  Dust Extraction
-  Fine Depth Adjustment
-  Bosh SDS System
-  Distortion-resistant protective guard
-  SDS-Plus Toolholder
-  Lithium-Ion Technology
-  SDS-Max Toolholder
-  Easy Fit
-  SDS-Plus Quick Exchange
-  Inox For a perfect finish on stainless steel
-  System Slim Grip
-  Kick Back
-  Vibration Control
-  Laser Class 2
-  Auto-Lock
-  Turbo Power
-  Woodrazor

Drill



Power Input	: 350 W
In Steel	: 6.5 mm
In Aluminum	: 6 mm
In Wood	: 15 mm
No-load Speed	: 0 – 4,000 rpm
Weight	: 1.1 kg



Power Input	: 450 W
In Steel	: 10 mm
In Aluminum	: 10 mm
In Wood	: 25 mm
No-load Speed	: 0 – 2,600 rpm
Weight	: 1.3 kg



Power Input	: 600 W
In Steel	: 13 mm
In Aluminum	: 13 mm
In Wood	: 30 mm
No-load Speed	: 0 – 2,600 rpm
Weight	: 1.65 kg



Power Input	: 550 W
In Steel	: 13 / 8 mm
In Wood	: 32 / 20 mm
No Load Speed : High	: 1,900 rpm
Low	: 1,000 rpm
Weight	: 1.9 kg



Power Input	: 550 W
In Steel	: 13 mm
In Aluminum	: 20 mm
In Wood	: 40 mm
No-load Speed	: 0 – 550 rpm
Torque (Approx.)	: 40 Nm
Weight	: 2.1 kg



Power Input	: 900 W
In Steel	: 16 / 8 mm
In Wood	: 20 / 13 mm
No Load Speed : High	: 0 - 1,200 rpm
Low	: 0 - 520 rpm
Weight	: 3.7 kg



Power Input	: 1,150 W
In Steel	: 23 / 13 mm
In Wood	: 50 / 35 mm
No Load Speed : High	: 0 - 640 rpm
Low	: 0 - 280 rpm
Weight	: 4.6 kg

BOSCH
Impact Drill



GSB 10 RE	
Power Input	: 500 W
In Masonry	: 10 mm
In Steel	: 8 mm
In Wood	: 20 mm
No-load Speed	: 0 – 2,600 rpm
Weight	: 1.5 kg



GSB 13 RE	
Power Input	: 600 W
In Masonry	: 13 mm
In Steel	: 10 mm
In Wood	: 25 mm
No-load Speed	: 0 – 2,800 rpm
Weight	: 1.65 kg



GSB 16 RE	
Power Input	: 701 W
In Masonry	: 16 mm
In Steel	: 13 mm
In Wood	: 30 mm
No-load Speed	: 0 – 3,000 rpm
Weight	: 1.9 kg

Cordless Drill / Screwdriver



GSB 20-2	
Power Input	: 701 W
In Concrete	: 20 / 13 mm
In Steel	: 13 / 8 mm
In Wood	: 40 / 25 mm
No-load Speed	: 1000 / 3000 rpm
No-load Impact Rate	: 16000 / 48000 bpm
Weight	: 2.2 kg



GSB 20-2 RE	
Power Input	: 701 W
In Concrete	: 20 / 13 mm
In Steel	: 13 / 8 mm
In Wood	: 40 / 25 mm
No-load Speed	: 0 – 1000/3000 rpm
No-load Impact Rate	: 0 – 16000/48000 bpm
Weight	: 2.2 kg



IXO II 3.6 V-Li	
Max. Screw Dia.	: 5 mm
Max. Torque	: 4 Nm
No-load Speed	: 0 – 180 rpm
Battery Voltage	: 3.6V / 1.3 Ah
Weight	: 0.3 kg

Cordless Drill / Screwdriver



GSR ProDrive (3.6V)	
Max. Screw Dia.	: 5 mm
Max. Torque	: 7 Nm
No-load Speed	: 0 – 250 rpm
Battery Voltage	: 3.6V / 1.3 Ah
Weight	: 0.5 kg



GSR 10.8 V-Li-2	
Drilling Dia. : In Steel	: 10 mm
In Wood	: 19 mm
Max. Torque	: 30 Nm
No-load Speed	: 0 – 400 / 1,100 rpm
Battery Voltage	: 10.8 V / 1.3 Ah
Weight	: 1.1 kg



GSR 7.2-2	
Drilling Dia. : In Steel	: 10 mm
In Wood	: 17 mm
Max. Torque	: 21 Nm
Max. Screw Dia.	: 6 mm
No-load Speed	: 0 – 400 / 1,100 rpm
Battery Voltage	: 7.2 V / 1.5 Ah
Weight	: 1.4 kg



GSR 9.6-2	
Drilling Dia. : In Steel	: 10 mm
In Wood	: 20 mm
Max. Torque	: 25 Nm
Max. Screw Dia.	: 6 mm
No-load Speed	: 0 – 400 / 1,000 rpm
Battery Voltage	: 9.6 V / 1.5 Ah
Weight	: 1.5 kg



GSR 12-2	
Drilling Dia. : In Steel	: 10 mm
In Wood	: 23 mm
Max. Torque	: 27 Nm
Max. Screw Dia.	: Up to 7 mm
No-load Speed	: 0 – 400 / 1,200 rpm
Battery Voltage	: 12 V / 1.5 Ah
Weight	: 1.6 kg



GSR 14.4-2	
Drilling Dia. : In Steel	: 10 mm
In Wood	: 26 mm
Max. Torque	: 30 Nm
Max. Screw Dia.	: 8 mm
No-load Speed	: 0 – 400 / 1,400 rpm
Battery Voltage	: 14.4 V / 1.5 Ah
Weight	: 1.7 kg

BOSCH

Cordless Impact Drill



GSB 14.4 VE-2-Li	
Clutch Settings	: 25+drilling
Max. Torque	: 80 Nm
No-load Speed	: 0 - 380 / 0 - 1,700 rpm
Battery Voltage	: 14.4 V / 2.6 Ah
Weight	: 2.3 kg

Cordless Impact Wrench



GDS 12 V	
Toolholder	: 1/2" external square
No-load Speed	: 0 - 2,800 rpm
Impact Rate	: 3,200 bpm
Max. Torque	: 175 Nm
Battery Voltage	: 12 V / 2.6 Ah
Weight	: 1.8 kg



GDS 14.4 V-Li	
Toolholder	: 1/2" external square
No-load Speed	: 0 - 2,800 rpm
Impact Rate	: 3,200 bpm
Max. Torque	: 160 Nm
Battery Voltage	: 14.4 V / 2.6 Ah
Weight	: 1.6 kg

Cordless Angle Driver



GWI 10.8 V-Li	
Drilling Dia. : In Steel In Wood	: 8 mm 10 mm
Max. Torque	: 13 Nm
Max. Screw Dia.	: 5 mm
No-load Speed	: 0 - 585 rpm
Battery Voltage	: 10.8 V / 1.3 Ah
Weight	: 1.1 kg

Cordless Impact Driver



GDR 10.8 V-Li	
Toolholder System	: 1/4" Hex (6.35 mm)
No-load Speed	: 0 - 1,800 rpm
Impact Rate	: 0 - 3,000 bpm
Max. Torque	: 100 Nm
Battery Voltage	: 10.8 V / 1.3 Ah
Weight	: 1.0 kg



GDR 12 V	
Toolholder System	: 1/4" Hex (6.35 mm)
No-load Speed	: 0 - 2,800 rpm
Impact Rate	: 0 - 3,200 bpm
Max. Torque	: 125 Nm
Battery Voltage	: 12 V / 2.0 Ah
Weight	: 1.8 kg



GDR 14.4 V-Li	
Toolholder System	: 1/4" Hex (6.35 mm)
No-load Speed	: 0 - 2,800 rpm
Impact Rate	: 0 - 3,200 bpm
Max. Torque	: 150 Nm
Battery Voltage	: 14.4 V / 2.6 Ah
Weight	: 1.6 kg

Cordless Multi-Cutter



GOP 10.8 V-Li	
Oscillation angle on left / right	: 1.4°
No-load Speed	: 5,000 - 20,000 rpm
Battery Voltage	: 10.8 V / 1.3 Ah
Weight	: 1.0 kg

Cordless Hammer



GBH 36 V-Li	
In Concrete	: 26 mm
In Steel	: 13 mm
In Wood	: 30 mm
Rated Speed	: 0 - 960 rpm
Impact Rate	: 0 - 4,260 bpm
Battery Voltage	: 36 V / 2.0 Ah
Weight	: 4.3 kg

Rotary Hammer with SDS-Plus



GBH 36 V-Li Compact	
In Concrete	: 4 - 18 mm
In Steel	: 13 mm
In Wood	: 30 mm
Rated Speed	: 0 - 1,500 rpm
Impact Rate	: 0 - 4,850 bpm
Battery Voltage	: 36 V / 1.3 Ah
Weight	: 2.9 kg



GBH 2-18 RE	
Power Input	: 550 W
In Concrete	: 18 mm
In Steel	: 13 mm
In Wood	: 30 mm
No-load Speed	: 450 - 1,550 rpm
Impact Rate	: 0 - 3,960 bpm
Weight	: 2.0 kg



GBH 2-22 E / GBH 2-22 RE *	
Power Input	: 620 W
In Concrete	: 22 mm
In Steel	: 13 mm
In Wood	: 30 mm
No-load Speed	: 0 - 1,000 rpm
Impact Rate	: 0 - 4,400 bpm
Weight	: 2.3 kg

BOSCH
Rotary Hammer with SDS-Plus



GBH 2-26 E / GBH 2-26 RE *

Power Input	: 800 W
In Concrete	: 4 - 26 mm
In Steel	: Up to 13 mm
In Wood	: Up to 30 mm
No-load Speed	: 0 - 900 rpm
Impact Rate	: 0 - 4,400 bpm
Weight	: 2.7 kg

Rotary Hammer with SDS-Plus



GBH 2-26 DFR

Power Input	: 800 W
In Concrete	: 4 - 26 mm
In Steel	: Up to 13 mm
In Wood	: Up to 30 mm
No-load Speed	: 0 - 900 rpm
Impact Rate	: 0 - 4,000 bpm
Weight	: 2.9 kg



GBH 2-23 REA

Power Input	: 710 W
In Concrete	: 4 - 23 mm
In Steel	: Up to 13 mm
In Wood	: Up to 30 mm
No-load Speed	: 0 - 1000 rpm
Impact Rate	: 0 - 4,400 bpm
Weight	: 2.9 kg / 3.6 kg



GBH 3-28 E

Power Input	: 720 W
Max. Bit Diameter	: 28 mm
Max. Core Bit Diameter	: 80 mm
No-load Speed	: 0 - 800 rpm
Impact Rate	: 0 - 4,000 bpm
Impact Force	: 0 - 3.3 J
Weight	: 3.3 kg



GBH 3-28 DFR

Power Input	: 800 W
In Concrete	: 28 mm
In Steel	: Up to 13 mm
In Wood	: Up to 30 mm
No-load Speed	: 0 - 900 rpm
Impact Rate	: 0 - 4,000 bpm
Weight	: 3.6 kg



GBH 4-32 DFR

Power Input	: 900 W
In Concrete	: 32 mm
In Steel	: Up to 13 mm
In Wood	: Up to 32 mm
No-load Speed	: 0 - 760 rpm
Impact Rate	: 0 - 3,600 bpm
Weight	: 4.7 kg

Rotary Hammer with SDS-Max



GBH 5-38 D

Power Input	: 1,050 W
Max. Bit Diameter	: 38 mm
Max. Core Bit Diameter	: 90 mm
No-load Speed	: 320 rpm
Impact Rate	: 0 - 2,900 bpm
Weight	: 5.8 kg



GBH 7-46 DE

Power Input	: 1,350 W
Max. Bit Diameter	: 45 mm
Max. Core Bit Diameter	: 150 mm
No-load Speed	: 145 - 280 rpm
Impact Rate	: 1,375 - 2,800 bpm
Impact Force	: 2 - 15 J
Weight	: 8.2 kg

Demolition Hammer



GSH 3 E

Power Input	: 650 W
Impact Rate	: 0 - 3,500 bpm
Impact Force	: 4.3 J
Weight	: 3.5 kg



GSH 388 / GSH 388 X *

Power Input	: 1,050 W
Impact Rate	: 2,800 bpm
Impact Force	: 8 - 10 J
Weight	: 4.9 kg



GSH 5 CE

Power Input	: 1,150 W
Impact Rate	: 1,300 - 2,900 bpm
Impact Force	: 2 - 13 J
Weight	: 6.2 kg



GSH 11 E

Power Input	: 1,500 W
Impact Rate	: 900 - 1,890 bpm
Impact Force	: 6 - 25 J
Weight	: 10.1 kg

BOSCH Demolition Hammer



GSH 16-30	
Power Input	: 1,750 W
Impact Rate	: 1,300 bpm
Impact Force	: 45 J
Weight	: 16.5 kg



GSH 27	
Power Input	: 1,900 W
Impact Rate	: 1,030 bpm
Impact Force	: 60 J
Weight	: 29 kg

Straight Grinder



GGS 27	
Power Input	: 500 W
Collet	: 6 mm
Grinding Points (Diameter)	: Max. 25 mm
No-load Speed	: 27,000 rpm
Weight	: 1.3 kg



GGS 27 L	
Power Input	: 500 W
Collet	: 6 mm
Grinding Points (Diameter)	: Max. 25 mm
No-load Speed	: 27,000 rpm
Weight	: 1.6 kg



GGS 6 S	
Power Input	: 1,200 W
Grinding Points (Diameter)	: Max. 125 mm
No-load Speed	: 6,800 rpm
Weight	: 1.8 kg

Angle Grinder



GWS 6-100	
Power Input	: 670 W
Grinding / Cutting Disc Diameter	: 100 mm
Wire Cup Brush Diameter	: 70 mm
No-load Speed	: 11,000 rpm
Weight	: 1.8 kg



GWS 7-100	
Power Input	: 720 W
Grinding / Cutting Disc Diameter	: 100 mm
Wire Cup Brush Diameter	: 70 mm
No-load Speed	: 11,000 rpm
Weight	: 1.8 kg



GWS 8-100 C	
Power Input	: 850 W
Grinding / Cutting Disc Diameter	: 100 mm
Wire Cup Brush Diameter	: 70 mm
No-load Speed	: 11,000 rpm
Weight	: 1.8 kg



GWS 8-100 CE	
Power Input	: 850 W
Grinding / Cutting Disc Diameter	: 100 mm
Wire Cup Brush Diameter	: 70 mm
No-load Speed	: 2,800 – 11,000 rpm
Weight	: 1.8 kg



GWS 11-125 CI	
Power Input	: 1,100 W
Grinding / Cutting Disc Diameter	: 125 mm
Wire Cup Brush Diameter	: 75 mm
No-load Speed	: 11,000 rpm
Weight	: 2 kg



GWS 14-125 INOX	
Power Input	: 1,400 W
Grinding / Cutting Disc Diameter	: 125 mm
Wire Cup Brush Diameter	: 70 mm
No-load Speed	: 2,500 – 7,500 rpm
Weight	: 2.2 kg



GWS 14-125 CI	
Power Input	: 1,400 W
Grinding / Cutting Disc Diameter	: 125 mm
Wire Cup Brush Diameter	: 70 mm
No-load Speed	: 11,000 rpm
Weight	: 2.2 kg



GWS 20-180	
Power Input	: 2,000 W
Grinding / Cutting Disc Diameter	: 180 mm
Wire Cup Brush Diameter	: 100 mm
No-load Speed	: 8,500 rpm
Weight	: 5.3 kg



GWS 20-230	
Power Input	: 2,000 W
Grinding / Cutting Disc Diameter	: 230 mm
Wire Cup Brush Diameter	: 100 mm
No-load Speed	: 6,500 rpm
Weight	: 5.6 kg

BOSCH Impact Wrench



GDS 18 E	
Power Input	: 500 W
Bolts KW	: M6 – M18
Torque	: 70 – 250 Nm
No-load Speed	: 500 – 1,300 rpm
Weight	: 16.2 kg

Paint Stirrer



GRW 11 E	
Power Input	: 1,150 W
No-load Speed	: 0 – 280 / 0 – 640 rpm
Tool Bolder	: 5/8"
Torque	: 105 / 50 Nm
Spindle Collar Diameter	: 43mm
Weight	: 4.2 kg

Bench Grinder



GSM 200	
Power Input	: 700 W
Grinding / Cutting Disc Diameter	: 200 mm
No-load Speed	: 2,800 rpm
Weight	: 16.2 kg

Shear



GSC 2.8	
Power Input	: 500 W
In Steel	: 2.8 mm
In Aluminium	: 3.5 mm
No-load Stroke Rate	: 2,400 rpm
Weight	: 2.7 kg

Screwdriver



GSR 6-25 TE	
Power Input	: 701 W
Self Tapping Screws	: Up to 6 mm diameter
No-load Speed	: 0 – 2,500 rpm
Weight	: 1.4 kg



GSR 6-45 TE	
Power Input	: 701 W
Self Tapping Screws	: Up to 6 mm diameter
No-load Speed	: 0 – 4,500 rpm
Weight	: 1.4 kg

Nibbler



GNA 2.0	
Power Input	: 500 W
Mild Steel	: 2.0 mm
Stainless Steel	: 1.0 mm
No-load Stroke Rate	: 2,400 stroke / min
Weight	: 2.0 kg

Diamond Wheel Cutter



GDM 12-34	
Power Input	: 1,250 W
Blade Diameter	: 110 mm
Max. Cutting Depth	: 34 mm
Base Plate	: 100 x 190 mm
No-load Speed	: 13,000 rpm
Weight	: 2.8 kg

Sabre Saw



GSA 900 E	
Power Input	: 900 W
Stroke Length	: 28 mm
No-load Stroke Rate	: 0 – 2,700 spm
Weight	: 3.4 kg



GSA 1100 E	
Power Input	: 1,100 W
Cutting Depth: In Wood / In Metal	: 230 mm / 20 mm
No-load Stroke Rate	: 0 – 2,700 spm
Weight	: 3.6 kg



GSA 1200 E	
Power Input	: 1,200 W
Stroke Length	: 19 mm / 32 mm
No-load Stroke Rate	: 0 – 2,800 spm
Weight	: 3.7 kg



GSA 1500 PCE	
Power Input	: 1,500 W
Cutting Depth: In Wood / In Metal	: 230 mm / 20 mm
No-load Stroke Rate	: 0 – 2,800 spm
Weight	: 4.3 kg

BOSCH



GST 65 / GST 65 E*

Power Input	: 400 W
In Wood	: 65 mm
In Steel	: 3 mm
No-load Stroke Rate	: 3,100 spm (GST 65) 500 – 3,100 spm (GST 65 E)
Weight	: 1.7 kg



GST 80 PBE

Power Input	: 580 W
In Wood	: 85 mm
In Steel	: 10 mm
No-load Stroke Rate	: 500 – 3,100 spm
Weight	: 2.4 kg

Circular Saw



GKS 190

Power Input	: 1,400 W
Blade Diameter	: 184 mm
Max. Cutting Capacities : 90° 45°	: 68 mm 48 mm
No-load Speed	: 5,500 rpm
Weight	: 4.1 kg

Cordless Circular Saw



GKS 18 V-Li

Blade Diameter	: 165 mm
Max. Cutting Capacities : 90° 50° 45°	: 52 mm 36 mm 40 mm
No-load Speed	: 3,900 rpm
Battery Voltage	: 18 V / 2.6 Ah
Weight	: 4.1 kg

Cut off Machine



GCO 2000

Power Input	: 2,000 W
Blade Diameter	: 355 mm
Max. Cutting Capacities : 90°	: 120 mm
No-load Speed	: 3,500 rpm
Weight	: 15.8 kg

Compound Mitre Saw



GCM 10

Power Input	: 1,800 W
Blade Size	: 254 mm
Arbour Size	: 25.4 / 30 mm
No-load Speed	: 4,500 rpm
Max. Mitre	: 48° L / 49° R
Cutting Capacities	: 89 x 95 mm
Weight	: 15 kg

Slide Metre Saw



GCM 800 S

Power Input	: 1,400 W
Blade Size	: 216 mm
Arbour Size	: 30 mm
No-load Speed	: 5,000 rpm
Max. Mitre	: 50° L / 58° R
Cutting Capacities	: 60 x 270 mm
Weight	: 15 kg



GCM 10-S

Power Input	: 1,800 W
Blade Size	: 254 mm
Bore Size	: 30 mm
No-load Speed	: 4,700 rpm
Max. Mitre	: 52° L / 62° R
Cutting Capacities	: 87 x 305 mm
Weight	: 21.5 kg

Combination Saw



GTM 12

Power Input	: 1,800 W
Blade Size	: 305 mm
Bore Size	: 30 mm
No-load Speed	: 4,300 rpm
Max. Mitre	: 48° L / 48° R
Cutting Capacities	: 95 x 151 mm
Weight	: 22 kg

Slide Mitre Saw



T1B

Length of work bench without extension	: 1,220 mm
Length of work bench with extension	: 2,630 mm
Weight	: 17 kg / 22 kg



T2B

Length of work bench with extension	: 2,510 mm
Weight	: 35 kg

Foam Cutter



GSG 300

Power Input	: 350 W
Cutting Capacity	: 300 mm
No-load Speed	: 3,200 spm
Weight	: 1.6 kg

BOSCH Planer



GHO 10-82	
Power Input	: 710 W
Planing Width	: 82 mm
Planing Depth	: 0 – 3.0 mm
No-load Speed	: 16,500 rpm
Weight	: 2.5 kg

Orbital Sander



GSS 230	
Power Input	: 190 W
Orbit Rate	: 24,000 opm
Sanding Plate	: 92 x 182 mm
Weight	: 1.4 kg



GSS 280 A	
Power Input	: 330 W
Orbit Rate	: 22,000 opm
Sand Paper Size	: 115 x 280 mm
Clamping Velcro	: 115 x 230 mm
Base Size	: 115 x 230 mm
Weight	: 2.6 kg

Eccentric Sander



GEX 125-1 AE	
Power Input	: 250 W
No-load Speed	: 7,500 – 12,000 opm
Oscillating Circuit Diameter	: 2.5 mm
Orbit Rate	: 15,000 – 24,000 opm
Sanding Plate	: 125 mm
Weight	: 1.3 kg

Belt Sander



GBS 75 A	
Power Input	: 710 W
No-load Speed	: 300 m/min
Sanding Surface	: 75 x 130 mm
Belt Size	: 75 x 533 mm
Weight	: 3.2 kg



GBS 100 A	
Power Input	: 1,200 W
Sanding Width	: 100 mm
Belt Length	: 610 / 620 mm
Belt Speed	: 450 m / min
Weight	: 6.2 kg

Blower



GBL 800 E	
Power Input	: 800 W
No-load Speed	: 16,000 rpm
Air Volume	: 4.5 m ³ /min
Weight	: 1.8 kg

Mini Router / Trimmer



GMR 1	
Power Input	: 550 W
Collet	: 6 mm or 1/4"
No-load Speed	: 33,000 rpm
Weight	: 1.5 kg

Hot Air Gun



GHG 600-3	
Power Input	: 1,800 W
Temperature	: 50 / 400 / 600°C
Air Flow	: 250 / 350 / 500 l/min
Weight	: 0.8 kg

Glue Gun



GHG 630 DCE	
Power Input	: 2,000 W
Temperature	: 50 - 630°C
Air Flow	: 150 / 300 / 500 l/min
Weight	: 0.9 kg

Glue Gun



GKP 200 CE	
Glue Capacity	: 30 g/min
No. of Heating Elements	: 2
Warming Up Time	: 4 min
Glue Stick Length	: 200 mm
Weight	: 0.4 kg

Wet & Dry Vacuum Cleaner



GAS 11-21	
Power Input	: 1,100 W
Container Volume	: 21 litre
Air Flow Max.	: 50 l/sec
Volume	: 150 mbar
Hose Diameter	: 35mm
Weight	: 6.3 kg

BOSCH Chain Saw



AKE 40-19 S	
Power Input	: 1,900 W
Blade Length	: 400 mm
Idling Cutting Speed	: 12 m/ sec
Weight	: 4.5 kg

Cordless Grass Shear



ISIO	
Batter Voltage	: 3.6 V
Blade Length	: 80 mm
Weight	: 0.5 kg

Grass Trimer



ART 23 EASYTRIM	
Motor Power	: 280 W
Cutting Diameter	: 230 mm
Line Feed	: "Pro-Tap"
Line Thickness	: 1.6 mm x 8 m
Line Capacity	: 8 m
Cable Length	: 10 m
Weight	: 1.6 kg



ART 23 COMBITRIM	
Motor Power	: 400 W
Cutting Diameter	: 230 mm
Line Feed	: "Pro-Tap"
Line Thickness	: 1.6 mm x 8 m
Extra Line	: Diameter 2.4 mm
Line Capacity	: 8 m
Weight	: 2.7 kg

Cordless Secatuer



CSIO	
Batter Voltage	: 3.6 V
Max. Cutting Capacity	: 14 mm diameter
Cutting System	: Bypass
Weight	: 0.6 kg

Hand Mower



AHM 30	
Width of Cut	: 30 cm
Height of Cut	: 12 - 40 mm
Cutting Adjustment	: Variable
Cylinder Blader	: 4
Weight	: 6.4 kg

Cylinder Mower



ASM 32	
Motor Output	: 360 W
Width of Cut	: 32 cm
Height of Cut	: 12 - 32 mm
Cutting Height Adjustment	: 5 Stages
Grass Collecting Box	: 31 L
Weight	: 11 kg

Hedge-Cutter



AHS 480-24 T	
Motor Output	: 550 W
Cut Length	: 480 cm
Blade Spacing	: 24 mm
Stroke Rate	: 2,800 rpm
Weight	: 3.9 kg

Rotary Lawn Mower



ROTAK 320	
Motor Output	: 1,000 W
Width of Cut	: 32 cm
Height of Cut	: 32 - 60 mm (3 Settings)
Grass Collecting Box	: 28 L
Weight	: 7 kg



ROTAK 34	
Motor Output	: 1,300 W
Width of Cut	: 34 cm
Height of Cut	: 20 - 70 mm
Grass Collecting Box	: 40 L
Weight	: 11 kg

Cordless Rotary Lawn Mower



ROTAK 37 Li	
Battery Voltage	: 36 V
Width of Cut	: 37 cm
Height of Cut	: 20 - 70 mm
Grass Collecting Box	: 40 L
Weight	: 13 kg

Laser Rangefinder



DLE 40	
Laser Diode	: 635 nm, < 1mW
Laser Class	: 2
Measuring Range	: 0.05 - 40m
Measuring Accuracy.	: ±1.5
Measuring Units	: m/cm, ft/inches
Batteries	: 4 x 1.5V LR03 (AAA)
Weight	: 175 g

BOSCH Laser Rangefinder



ALQ 0106

Laser Diode	: 635 nm, < 1mW
Laser Class	: 2
Measuring Range	: 0.05 - 70m
Measuring Accuracy	: ±1.5
Measuring Units	: m/cm, ft/inches
Batteries	: 4 x 1.5V LR03 (AAA)
Weight	: 180 g



ALQ 0107

Laser Diode	: 635 nm, < 1mW
Laser Class	: 2
Measuring Range	: 0.30 - 150m
Measuring Accuracy	: ± 2
Measuring Units	: m/cm, ft/inches
Batteries	: 4 x 1.5V LR06 (AAA)
Weight	: 400 g

Detector



ALQ 0108

Max. Measuring Depth	: 100mm
Accuracy	: ± 5 mm
Power Supply	: 4 x 1.5V LR6 (AA)
Detectable Materials	: Plastic pipes, Cables of all kinds, Ferrous / Non-ferrous Metals, Wood, Cavities
Weight	: 0.8 kg

All-Purpose Detector



ALQ 0109

Max. Measuring Depth	
Ferrous Metals	: 100mm
Non-Ferrous Metals	: 80 mm
Accuracy	: ± 5 mm
Copper Conductors	: 50 mm
Wood	: 20 mm
Weight	: 240 g

High Pressure Cleaner



ALQ 0110

Motor Power	: 1,450 W
Max. Pressure	: 100 bar
Max. Flow Volume	: 340 l/h
Max. Flow Temp.	: 40°C
Weight	: 6 kg



ALQ 0111

Motor Power	: 1,750 W
Max. Pressure	: 120 bar
Max. Flow Volume	: 390 l/h
Max. Flow Temp.	: 60°C
Weight	: 13 kg



ALQ 0112

Motor Power	: 2,700 W
Max. Pressure	: 150 bar
Max. Flow Volume	: 530 l/h
Max. Flow Temp.	: 60°C
Weight	: 19 kg



ALQ 0113

Motor Power	: 2,800 W
Max. Pressure	: 155 bar
Max. Flow Volume	: 570 l/h
Max. Flow Temp.	: 60°C
Weight	: 29.1 kg

Digital Inclinator



ALQ 0114

Length	: 600 mm
Measuring Range	: 360° (4° x 90°)
Measuring Accuracy	: electronic at 0°/90°: +0.05°
Batteries Performance	: approx 200 h
Weight	: 0.7 kg



ALQ 0115

Length	: 1200 mm
Measuring Range	: 360° (4° x 90°)
Measuring Accuracy	: Electronic at 0°/90°: +0.05°
Display of measurements result	: % or mm/m
Automatic deactivation	: approx. 5min
Power Supply	: 1 x 9 V 6LR61
Weight	: 1.3 kg

Line Laser



ALQ 0116

Laser Diode	: 635 nm, < 1mW
Laser Class	: 2
Working Range	: 20 m
Working Range With Receiver	: 50 m
Leveling Accuracy	: ± 0.3 mm / m
Batteries	: 3 x 1.5V LR6 (AAA)
Weight	: 0.45 kg

Laser Level



ALQ 0117

Laser Diode	: 635 nm, < 1mW
Laser Class	: 2
Accuracy	: ± 0.2 mm / m
Accuracy between 45° and 90° -Line	: ± 0.4 mm / m
Batteries	: 4 x 1.5V LR06 (AAA)
Weight	: 0.5 kg

BOSCH Point Laser



Laser Diode	: 635 nm, < 1mW
Laser Class	: 2
Working Range	: 30m
Self-leveling Range	: ± 3° / ± 5°
Leveling Accuracy.	: ± 0.3 mm / m
Batteries	: 3 x 1.5V LR6 (AAA)
Weight	: 0.25 kg

Rotation Laser Level



Laser Diode	: 635 nm, < 1mW
Laser Class	: 2
Working Range	: 30m
Working Range With Receiver	: 150 m
Leveling Accuracy.	: ± 0.1 mm / m
Batteries	: 4 x 1.5V LR20 (D)
Weight	: 1.8 kg

Digital Spirit Level



Measurement Range	: 0 – 220°
Electronics Measurement Accuracy, Angles	: ± 0.1° ± 1.8 mm/m
Electronics Measurement Accuracy, Vials	: ± 0.057° ± 1 mm/m
Power supply	: 4 x 1.5V LR6 (AA)
Weight	: 1.1 kg

SKIL Jigsaw



Jigsaw 4160
Specifications

Input Power	: 400 W
Blade Holder	: 'Click', T-shank & U-shank
Saw Blade Guide Roller	: yes
Switch	: on/off, 2 finger trigger
Lock On	: left + right side
Foot Adjustability	: 'Click', 0° and 45°
Capacity in Wood	: 65mm
Capacity in Aluminium	: 10mm
Capacity in Steel	: 4mm
Length of Stroke	: 16mm
Blade Speed	: 2,850 /min

Impact Drill



Impact Drill 6002
Specifications

Input Power	: 450 W
Chuck Type	: 10 mm, keyed
No-load Speed	: 0 - 3,000 rpm
Capacity in Steel	: 10 mm
Capacity in Masonry	: 16 mm
Capacity in Wood	: 30 mm

- Standard equipment
- Plastic carrying case
 - 16 pcs. drill and screw bits
 - Chuck key



Impact Drill 6006
Specifications

Input Power	: 550 W
Chuck Type	: 13 mm, keyed
No-load Speed	: 0 - 3,000 rpm
Capacity in Steel	: 13 mm
Capacity in Masonry	: 16 mm
Capacity in Wood	: 35 mm

- Standard equipment
- Plastic carrying case
 - Side handle
 - 16 pcs. drill and screw bits
 - Chuck key
 - Depth gauge

Sander



Sander 7310
Specifications

Sanding surface	: 92 x 185 mm
Sanding sheet size	: 93 x 230 mm
Sanding mov. p.m. (no load)	: 24,000
Sanding orbit Ø	: 2.0mm
Input power	: 160 W
Weight	: 1.5 kg

- Standard equipment
- Dust suction adapter
 - 3 sanding sheets grit 120

Angle Grinder



Angle Grinder 9133
Specifications

Power	: 620 W
RPM	: 11,000 rpm
Disc Diameter	: 100 mm
Spindle Thread	: M 10
Capacity in Wood	: 1.45 kg

- Standard equipment
- Set of flanges
 - Safety guard

Cordless Screwdriver



Cordless Screwdriver 2240
Specifications

Voltage	: 12 V
No-load Speed	: 0 - 700 rpm
Max. Torque	: 15 Nm
Torque Settings	: 5 + 1
Switch	: VSR
Charging Time	: 1 hr
Battery Capacity	: 1.2 Ah
Weight	: 1.4 kg

- Standard equipment
- Plastic carrying case
 - Magnetic bit holder
 - 6 pcs. screw bit set
 - Electronic brake
 - Extra battery
 - 6 pcs. drill bit set
 - 1 hour charger
 - Soft grip



Cordless Screwdriver 2236
Specifications

Voltage	: 3.6 V
No-load Speed	: 180 rpm
Max. Torque	: 4 Nm
Capacity Screws	: 6 mm
Charger	: 3 - 5 hrs
Hex - drive	: 6.35mm
Weight	: 0.45 kg

- Standard equipment
- 3-5 hours charger
 - Magnetic bit holder
 - Plastic carrying case
 - 2mm hex-drill bit
 - 3.6V (1.2Ah NiCd) battery
 - Double-ended screw bit (PH2 - 5.5)
 - 10 additional screw bits (PZ1, 2, 3, PH1, 2, 3, S4, 6, T20, 25)



Circular Saw 5300
Specifications

Power	: 1,300 W
RPM	: 4,500 rpm
Blade Size	: 184 mm = 7 1/4"
Depth of Cut at 90°	: 62 mm
Bevel Cut	: 0 - 45°
Weight	: 4.9 kg

- Standard equipment
- 184mm TCT blade
 - Parallel guide
 - Blade wrench for easy blade changing

Hot Air Gun



Hot Air Gun 8003
Specifications

Input power	: 1,800 W
Output temperature setting 1	: 150°C
Output temperature setting 2	: 400°C
Output temperature setting 3	: 570°C
Airflow setting 1	: 250 l/min
Airflow setting 2	: 250 l/min
Airflow setting 3	: 500 l/min
Weight	: 0.7 kg

- Standard equipment
- Durable plastic case
 - 1 reduction nozzle
 - 1 glass protection nozzle
 - 1 reflector nozzle
 - 1 flat nozzle